

GBU4A THRU GBU4M

List

List.....	1
Package outline.....	2
Features.....	2
Mechanical data.....	2
Maximum ratings and Electrical characteristics	2
Rating and characteristic curves.....	3
Pinning information.....	4
Marking.....	4
Tube packing & Bulk packing.....	4
Suggested thermal profiles for soldering processes.....	5
High reliability test capabilities.....	6

GBU4A THRU GBU4M

4.0A Glass Passivated Single-Phase Bridge Rectifiers 50V-1000V


Features

- Surge overload ratings to 150 amperes peak
- Recommended for non-automatic applications
- Ideal for & save space on printed circuit board.
- Applicable for automatic insertion
- Reliable low cost construction utilizing molded plastic technology results in inexpensive product
- Glass passivated chip junctions
- Lead-free parts meet RoHS requirements
- UL recognized file # E321971
- Suffix "-H" indicates Halogen free parts, ex. GBU4A-H

Mechanical data

- Epoxy:UL94-V0 rated flame retardant
- Case : Molded plastic, GBU
- Terminals : Solder plated, solderable per
MIL-STD-750, Method 2026
- Polarity : marked on body
- Mounting Position : Any
- Weight : Approximated 4.00 gram

Package outline



Maximum ratings and Electrical characteristics (AT $T_A=25^{\circ}\text{C}$ unless otherwise noted)

PARAMETER	CONDITIONS	Symbol	MIN.	TYP.	MAX.	UNIT
Forward rectified current	(with heatsink Note 1) at $T_c=100^{\circ}\text{C}$ (without heatsink)	I_o			4.0 2.4	A
Forward surge current	8.3ms single half sine-wave (JEDEC methode)	I_{FSM}			150	A
Reverse current per diode	$V_R = V_{RRM} \quad T_J = 25^{\circ}\text{C}$	I_R			10.0	μA
	$V_R = V_{RRM} \quad T_J = 125^{\circ}\text{C}$				500	
I^2t Rating for fusing	$t < 8.3 \text{ ms}$	I^2t			93.4	A^2s
Typical junction capacitance per diode	Measured at 1.0MHz and applied reverse voltage of 4.0 VDC	C_J		45		pF
Typical thermal resistance	Junction to case	$R_{\theta JC}$		2.2		$^{\circ}\text{C/W}$
Storage temperature		T_{STG}	-55		+150	$^{\circ}\text{C}$

Note 1. Device mounted on 50mm*50mm*1.6mm Cu plate heatsink.

SYMBOLS	V_{RRM}^{*1} (V)	V_{RMS}^{*2} (V)	V_R^{*3} (V)	V_F^{*4} (V)	Operating temperature $T_J, (^{\circ}\text{C})$
GBU4A	50	35	50	1.10	-55 to +150
GBU4B	100	70	100		
GBU4D	200	140	200		
GBU4G	400	280	400		
GBU4J	600	420	600		
GBU4K	800	560	800		
GBU4M	1000	700	1000		

*1 Repetitive peak reverse voltage

*2 RMS voltage

*3 Continuous reverse voltage

*4 Maximum forward voltage per diode@ $I_F=4.0\text{A}$

Rating and characteristic curves (GBU4A THRU GBU4M)

Fig.1 - Forward Current Derating Curve




Fig.2 - Maximum Non-Repetitive Surge Current




Fig.3 - Typical Reverse Characteristics




Fig.4 - Typical Forward Characteristics







Fig.5 - Typical Junction Capacitance



GBU4A THRU GBU4M

Pinning information

Simplified outline	Symbol
	

Marking


Type number	Marking code
GBU4A	GBU4A
GBU4B	GBU4B
GBU4D	GBU4D
GBU4G	GBU4G
GBU4J	GBU4J
GBU4K	GBU4K
GBU4M	GBU4M

Tube packing

PACKAGE	TUBE (pcs)	TUBE SIZE (m/m)	CARTON SIZE (m/m)	CARTON (pcs)	APPROX. GROSS WEIGHT (kg)
GBU	20	474*42*7	496*225*90	1,000	6.5

BULK PACKING

DEVICE CASE TYPE	Q'TY 1 (PCS / BOX)	INNER BOX SIZE (m/m)	CARTON SIZE (m/m)	Q'TY 2 (PCS / CARTON)	APPROX. CROSS WEIGHT(kg)
GBU	800	350 * 337 * 44	375 * 360 * 213	3,200	16.9

GBU4A THRU GBU4M**Suggested thermal profiles for soldering processes****1. Lead free temperature profile wave-soldering**

GBU4A THRU GBU4M

High reliability test capabilities

Item Test	Conditions	Reference
1. Solder Resistance	at $260 \pm 5^{\circ}\text{C}$ for $10 \pm 2\text{sec.}$ immerse body into solder $1/16'' \pm 1/32''$	MIL-STD-750D METHOD-2031
2. Solderability	at $245 \pm 5^{\circ}\text{C}$ for 5 sec.	MIL-STD-202F METHOD-208
3. High Temperature Reverse Bias	$V_R = 80\%$ rate at $T_J = 150^{\circ}\text{C}$ for 168 hrs.	MIL-STD-750D METHOD-1038
4. Forward Operation Life	Rated average rectifier current at $T_A = 25^{\circ}\text{C}$ for 500hrs.	MIL-STD-750D METHOD-1027
5. Intermittent Operation Life	$T_A = 25^{\circ}\text{C}$, $I_F = I_O$ On state: power on for 5 min. off state: power off for 5 min. on and off for 500 cycles.	MIL-STD-750D METHOD-1036
6. Pressure Cooker	$15P_{SIG}$ at $T_A = 121^{\circ}\text{C}$ for 4 hrs.	JESD22-A102
7. Temperature Cycling	-55°C to $+125^{\circ}\text{C}$ dwelled for 30 min. and transferred for 5min. total 10 cycles.	MIL-STD-750D METHOD-1051
8 Forward Surge	8.3ms single half sine-wave , one surge.	MIL-STD-750D METHOD-4066-2
9. Humidity	at $T_A = 85^{\circ}\text{C}$, RH=85% for 1000hrs.	MIL-STD-750D METHOD-1021
10. High Temperature Storage Life	at 175°C for 1000 hrs.	MIL-STD-750D METHOD-1031