

FMBTRC245S-Q1

List

List.....	1
Package outline.....	2
Features.....	2
Mechanical data.....	2
Maximum ratings	2
Electrical characteristics.....	2
Rating and characteristic curves.....	3
Pinning information.....	4
Marking.....	4
Suggested solder pad layout.....	4
Packing information.....	5
Reel packing.....	6
Suggested thermal profiles for soldering processes.....	6

FMBTRC245S-Q1

NPN Silicon Epitaxial Planar Digital Transistor


Features

- For Switching and interface circuit and drive circuit applications.
- With built-in bias resistors.
- Simplify circuit design.
- Reduce a quantity of parts and manufacturing process.
- High output current.
- We declare that the material of product compliance with RoHS requirements.
- Qualified to AEC-Q101 standards for high reliability.
- Suffix "-H" indicates Halogen free parts, ex. FMBTRC245S-Q1-H.

Mechanical data

- Epoxy:UL94-V0 rated flame retardant
- Case : Molded plastic, SOT-23
- Terminals : Solder plated, solderable per MIL-STD-750, Method 2026
- Mounting Position : Any

Package outline



Maximum ratings (AT $T_A=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Output voltage	V_o	50	V
Input voltage	V_i	30, -5	V
Output current	I_o	800	mA
Power dissipation	P_{tot}	200	mW
Junction temperature	T_j	150	$^{\circ}\text{C}$
Storage temperature range	T_{stg}	-55 to +150	$^{\circ}\text{C}$

Electrical characteristics (AT $T_A=25^{\circ}\text{C}$ unless otherwise noted)


Parameter	Conditions	Symbol	Min.	Typ.	Max.	Unit
DC current gain	$V_o=5\text{V}$, $I_o=50\text{mA}$	h_{FE}	56			
Output cut-off current	$V_o=30\text{V}$	$I_{O(OFF)}$			10	μA
Input current	$V_i=5\text{V}$	I_i			7.2	mA
Output voltage	$I_o=50\text{mA}$, $I_i=2.5\text{mA}$	$V_{O(ON)}$			0.3	V
Input voltage (ON)	$V_o=0.3\text{V}$, $I_o=20\text{mA}$	$V_{I(ON)}$			3	V
Input voltage (OFF)	$V_o=5\text{V}$, $I_o=0.1\text{mA}$	$-V_{(OFF)}$	0.3			V
Transition frequency	$V_o=10\text{V}$, $I_o=5\text{mA}$, $f=100\text{MHz}$ (Note 1)	f_T		200		MHZ
Input resistance		R_1		1		K Ω
Base Emitter resistance		R_2		10		K Ω

Note :


1.Characteristic of transistor only.

Rating and characteristics curves(FMBTRC245S-Q1)


$I_o - V_{I(ON)}$



$I_o - V_{I(OFF)}$





$G_i - I_o$





FMBTRC245S-Q1

Pinning information


Pin	Simplified outline	Symbol
Pin1 Base Pin2 Emitter Pin3 Collector		

Marking

Type numbe	Marking code
FMBTRC245S-Q1	 or 

Suggested solder pad layout


SOT-23



Dimensions in inches and (millimeters)

FMBTRC245S-Q1

Packing information



unit:mm

Item	Symbol	Tolerance	SOT-23
Carrier width	A	0.1	3.15
Carrier length	B	0.1	2.77
Carrier depth	C	0.1	1.22
Sprocket hole	d	0.1	1.50
13" Reel outside diameter	D	2.0	-
13" Reel inner diameter	D1	min	-
7" Reel outside diameter	D	2.0	178.00
7" Reel inner diameter	D1	min	55.00
Feed hole diameter	D2	0.5	13.00
Sprocket hole position	E	0.1	1.75
Punch hole position	F	0.1	3.50
Punch hole pitch	P	0.1	4.00
Sprocket hole pitch	P0	0.1	4.00
Embossment center	P1	0.1	2.00
Overall tape thickness	T	0.1	0.23
Tape width	W	0.3	8.00
Reel width	W1	1.0	12.0

Note: Devices are packed in accordance with EIA standard RS-481-A and specifications listed above.


FMBTRC245S-Q1

Reel packing

PACKAGE	REEL SIZE	REEL (pcs)	COMPONENT SPACING (m/m)	BOX (pcs)	INNER BOX (m/m)	REEL DIA, (m/m)	CARTON SIZE (m/m)	CARTON (pcs)	APPROX. GROSS WEIGHT (kg)
SOT-23	7"	3,000	4.0	30,000	183*123*183	178	382*257*387	240,000	11.6

Suggested thermal profiles for soldering processes

- 1.Storage environment: Temperature=5°C~40°C Humidity=55%±25%
- 2.Reflow soldering of surface-mount devices



3.Reflow soldering

Profile Feature	Soldering Condition
Average ramp-up rate(T _L to T _P)	<3°C/sec
Preheat -Temperature Min(T _{smín}) -Temperature Max(T _{smáx}) -Time(min to max)(t _s)	150°C 200°C 60~120sec
T _{smáx} to T _L -Ramp-upRate	<3°C/sec
Time maintained above: -Temperature(T _L) -Time(t _L)	217°C 60~260sec
Peak Temperature(T _P)	255°C-0/+5°C
Time within 5°C of actual Peak Temperature(t _p)	10~30sec
Ramp-down Rate	<6°C/sec
Time 25°C to Peak Temperature	<6minutes