

ESD5Z15A

List

List.....	1
Package outline.....	2
Features.....	2
Applications.....	2
Mechanical data.....	2
Maximum ratings	2
Electrical characteristics.....	2
Rating and characteristic curves.....	3
Pinning information.....	4
Marking.....	4
Suggested solder pad layout.....	4
Packing information.....	5
Reel packing.....	6
Suggested thermal profiles for soldering processes.....	6
High reliability test capabilities.....	7

ESD5Z15A

Surface Mount Uni-Directional TVS For ESD Protection Diode 15V

Features

- Protects one line.
- Ultra low leakage.
- Operating voltage : 15V.
- Low clamping voltage.
- Provide transient protection :
IEC 61000-4-2 (ESD) $\pm 30\text{kV}$ (Air & Contact).
IEC 61000-4-5 (Lightning) 11A (8/20 μs).
- Lead-free parts meet RoHS requirements.
- Suffix "-H" indicates Halogen-free part, ex.ESD5Z15A-H.


Applications

- Cellular Handsets & Accessories
- Personal Digital Assistants (PDAs)
- Notebooks, Desktops, Servers.
- Portable Instrumentation.
- Analog Inputs.

Mechanical data

- Epoxy:UL94-V0 rated flame retardant
- Case : Molded plastic, SOD-523FL
- Terminals : Solder plated, solder able per
MIL-STD-750, Method 2026
- Polarity : Indicated by cathode band
- Mounting Position : Any
- Weight : Approximated 0.002 gram

Package outline



Maximum ratings (At $T_A=25^\circ\text{C}$ unless otherwise noted)


Parameter	Symbol	Value	Unit
Peak pulse power ($t_p=8/20\mu\text{s}$)	P_{PP}	350	W
Peak pulse current ($t_p=8/20\mu\text{s}$)	I_{PP}	11	A
ESD Per IEC 61000-4-2 (Air)	V_{ESD}	± 30	KV
ESD Per IEC 61000-4-2 (Contact)		± 30	
Operating temperature	T_J	+125	$^\circ\text{C}$
Storage temperature	T_{stg}	-55 to +150	$^\circ\text{C}$

Electrical characteristics (At $T_A=25^\circ\text{C}$ unless otherwise noted)


Parameter	Conditions	Symbol	Min.	Typ.	Max.	Unit
Reverse stand-off voltage		V_{RWM}			5.0	V
Breakdown voltage	$I_T=1\text{mA}$	V_{BR}	18			V
Reverse leakage current	$V_{RWM}=15\text{V}$	I_R			0.2	μA
Clamping voltage	$I_{PP}=1\text{A}$ ($t_p=8/20\mu\text{s}$)	V_C			23	V
	$I_{PP}=11\text{A}$ ($t_p=8/20\mu\text{s}$)	V_C			32	V
Junction capacitance	$V_R=0\text{V}$, $f=1\text{MHz}$	C_J			80	pF

ESD5Z15A


Rating and characteristic curves




Junction Capacitance vs. Reverse Voltage





Peak Pulse Power vs. Pulse Time



Clamping Voltage vs. Peak Pulse Current



Power Derating Curve

8 X 20 μ s Pulse Waveform

Note: Data is taken with a 10x attenuator

ESD Clamping Voltage

+8 kV Contact per IEC61000-4-2

ESD5Z15A


Pinning information

Pin	Simplified outline	Symbol
Pin1 cathode Pin2 anode		

Marking

Type number	Marking code
ESD5Z15A	15E

Suggested solder pad layout




Dimensions in inches and (millimeters)

PACKAGE	A	B	C
SOD-523FL	0.032 (0.80)	0.024 (0.60)	0.044 (1.10)

ESD5Z15A

Packing information



unit:mm

Item	Symbol	Tolerance	SOD-523FL
Carrier width	A	0.1	0.90
Carrier length	B	0.1	1.94
Carrier depth	C	0.1	0.76
Sprocket hole	d	0.1	1.50
7" Reel outside diameter	D	2.0	178.00
7" Reel inner diameter	D ₁	min	50.00
Feed hole diameter	D ₂	0.2	13.00
Sprocket hole position	E	0.1	1.75
Punch hole position	F	0.1	3.50
Punch hole pitch	P	0.1	2.00
Sprocket hole pitch	P ₀	0.1	4.00
Embossment center	P ₁	0.1	2.00
Overall tape thickness	T	0.1	0.23
Tape width	W	0.3	8.00
Reel width	W ₁	1.0	9.50

Note: Devices are packed in accordance with EIA standard RS-481-A and specifications listed above.


ESD5Z15A

Reel packing

PACKAGE	REEL SIZE	REEL (pcs)	COMPONENT SPACING (m/m)	BOX (pcs)	INNER BOX (m/m)	REEL DIA, (m/m)	CARTON SIZE (m/m)	CARTON (pcs)	APPROX. GROSS WEIGHT (kg)
SOD-523FL	7"	5,000	2.0	50,000	183*123*183	178	382*257*387	400,000	13.5

Suggested thermal profiles for soldering processes

- 1.Storage environment: Temperature=5°C~40°C Humidity=55%±25%
- 2.Reflow soldering of surface-mount devices



3.Reflow soldering

Profile Feature	Soldering Condition
Average ramp-up rate(T _L to T _P)	<3°C/sec
Preheat -Temperature Min(T _{smín}) -Temperature Max(T _{smáx}) -Time(min to max)(t _s)	150°C 200°C 60~120sec
T _{smáx} to T _L -Ramp-upRate	<3°C/sec
Time maintained above: -Temperature(T _L) -Time(t _L)	217°C 60~260sec
Peak Temperature(T _P)	255°C-0/+5°C
Time within 5°C of actual Peak Temperature(t _P)	10~30sec
Ramp-down Rate	<6°C/sec
Time 25°C to Peak Temperature	<6minutes

ESD5Z15A

High reliability test capabilities

Item Test	Conditions	Reference
1. Solder Resistance	at $260\pm 5^{\circ}\text{C}$ for $10\pm 2\text{sec.}$	MIL-STD-750D METHOD-2031
2. Solderability	at $245\pm 5^{\circ}\text{C}$ for 5 sec.	MIL-STD-202F METHOD-208
3. High Temperature Reverse Bias	$V_{\text{BR}}=V_{\text{BR MIN}}*80\%$ at $T_{\text{J}}=125^{\circ}\text{C}$ for 168 hrs.	MIL-STD-750D METHOD-1038
4. Pressure Cooker	$15P_{\text{SIG}}$ at $T_{\text{A}}=121^{\circ}\text{C}$ for 4 hrs.	JESD22-A102
5. Temperature Cycling	-55°C to $+125^{\circ}\text{C}$ dwelled for 30 min. and transferred for 5min. total 10 cycles.	MIL-STD-750D METHOD-1051
6. Humidity	at $T_{\text{A}}=85^{\circ}\text{C}$, RH=85% for 1000hrs.	MIL-STD-750D METHOD-1021
7. High Temperature Storage Life	at 175°C for 1000 hrs.	MIL-STD-750D METHOD-1031