

ESDHP3Z5.0

List

List.....	1
Package outline.....	2
Features.....	2
Applications.....	2
Mechanical data.....	2
Maximum ratings	2
Electrical characteristics.....	2
Rating and characteristic curves.....	3
Pinning information.....	4
Marking.....	4
Suggested solder pad layout.....	4
Package Information.....	5
Reel packing.....	6
Suggested thermal profiles for soldering processes.....	6

ESDHP3Z5.0

Surface Mount Uni-Directional TVS For ESD Protection Diode : 5V

Features

- 1800W peak pulse power (8/20 μ s).
- Protects one power line or data line.
- High peak pulse current capability.
- Complies with following standards:
- IEC 61000-4-2 (ESD) immunity test : Air discharge: ± 30 kV.
Contact discharge: ± 30 kV.
- IEC61000-4-5 (Lightning) 120A (8/20 μ s).
- Lead-free parts meet RoHS requirements.
- Suffix "-H" indicates Halogen-free part, ex.ESDHP3Z5.0-H.


Applications

- Mobile Phones and Accessories.
- Power Supply Protection.

Mechanical data

- Epoxy:UL94-V0 rated flame retardant.
- Case : Molded plastic, SOD-323F.
- Terminals : Solder plated, solderable per MIL-STD-750, Method 2026.
- Mounting Position : Any.
- Weight : Approximated 0.005 gram.

Package outline



Maximum ratings (At $T_A=25^{\circ}\text{C}$ unless otherwise noted)





Parameter	Symbol	Value	Unit
Peak pulse power ($t_p = 8/20\mu\text{s}$)	P_{PK}	1800	W
Peak Pulse Current ($t_p = 8/20\mu\text{s}$), (Pin 1 to Pin 2)	I_{PP}	120	A
ESD Per IEC 61000-4-2 (Air)	V_{ESD}	± 30	KV
ESD Per IEC 61000-4-2 (Contact)		± 30	
Operating temperature range	T_J	-55 to +125	$^{\circ}\text{C}$
Storage temperature range	T_{STG}	-55 to +150	$^{\circ}\text{C}$

Electrical characteristics (At $T_A=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Reverse working voltage	V_{RWM}				5.0	V
Breakdown voltage	V_{BR}	$I_T = 1\text{mA}$	6.0			V
Reverse leakage current	I_R	$V_{RWM} = 5\text{V}$			1	μA
Clamping voltage	V_C	$I_{PP} = 20\text{A}$ ($t_p = 8/20\mu\text{s}$)			9.5	V
		$I_{PP} = 120\text{A}$ ($t_p = 8/20\mu\text{s}$)			15	
Junction capacitance	C_J	$V_R = 0\text{V}$, $f = 1\text{MHz}$		450		pF


ESDHP3Z5.0

Rating and characteristic curves




Clamping Voltage vs. Peak Pulse Current (tp = 8/20μs)

Power Derating Curve



8 X 20μs Pulse Waveform




Note: Data is taken with a 10x attenuator
ESD Clamping Voltage
8 kV Contact per IEC61000-4-2

ESDHP3Z5.0


Pinning information

Pin Configuration	Simplified outline	Symbol
Pin 1 Cathode Pin 2 Anode		

Marking



Suggested solder pad layout




Dimensions in inches and (millimeters)

PACKAGE	A	B	C
SOD-323F	0.031 (0.80)	0.031 (0.80)	0.056 (1.40)

ESDHP3Z5.0

Packing information



unit:mm

Item	Symbol	Tolerance	SOD-323F
Carrier width	A	0.1	1.48
Carrier length	B	0.1	3.30
Carrier depth	C	0.1	1.25
Sprocket hole	d	0.1	1.50
13" Reel outside diameter	D	2.0	-
13" Reel inner diameter	D ₁	min	-
7" Reel outside diameter	D	2.0	178.00
7" Reel inner diameter	D ₁	min	55.00
Feed hole diameter	D ₂	0.5	13.00
Sprocket hole position	E	0.1	1.75
Punch hole position	F	0.1	3.50
Punch hole pitch	P	0.1	4.00
Sprocket hole pitch	P ₀	0.1	4.00
Embossment center	P ₁	0.1	2.00
Overall tape thickness	T	0.1	0.23
Tape width	W	0.3	8.00
Reel width	W ₁	1.0	9.50

Note: Devices are packed in accordance with EIA standard RS-481-A and specifications listed above.


ESDHP3Z5.0

Reel packing

PACKAGE	REEL SIZE	REEL (pcs)	COMPONENT SPACING (m/m)	BOX (pcs)	INNER BOX (m/m)	REEL DIA, (m/m)	CARTON SIZE (m/m)	CARTON (pcs)	APPROX. GROSS WEIGHT (kg)
SOD-323F	7"	3,000	4.0	30,000	183*123*183	178	382*257*387	240,000	8.0

Suggested thermal profiles for soldering processes

- 1.Storage environment: Temperature=5°C~40°C Humidity=55%±25%
- 2.Reflow soldering of surface-mount devices



3.Reflow soldering

Profile Feature	Soldering Condition
Average ramp-up rate(T _L to T _P)	<3°C/sec
Preheat -Temperature Min(T _{smIn}) -Temperature Max(T _{smax}) -Time(min to max)(t _s)	150°C 200°C 60~120sec
T _{smax} to T _L -Ramp-upRate	<3°C/sec
Time maintained above: -Temperature(T _L) -Time(t _L)	217°C 60~260sec
Peak Temperature(T _P)	255°C-0/+5°C
Time within 5°C of actual Peak Temperature(t _P)	10~30sec
Ramp-down Rate	<6°C/sec
Time 25°C to Peak Temperature	<6minutes