

FM201-AF THRU FM207-AF

List

List.....	1
Package outline.....	2
Features.....	2
Mechanical data.....	2
Maximum ratings	2
Rating and characteristic curves.....	3
Pinning information.....	4
Marking.....	4
Suggested solder pad layout.....	4
Packing information.....	5
Reel packing.....	6
Suggested thermal profiles for soldering processes.....	6
High reliability test capabilities.....	7

FM201-AF THRU FM207-AF

2.0A Surface Mount General Purpose Rectifiers 50V-1000V


Features

- For surface mounted applications
- Low reverse leakage
- Built-in strain relief, ideal for automated placement
- High forward surge current capability
- Lead free finish, RoHS compliant
- Suffix "-H" indicates Halogen-free parts, ex. FM201-AF-H.

Mechanical data

- Epoxy:UL94-V0 rated flame retardant
- Case : Molded plastic, DO-214AC / SMA-F
- Terminals : Solder plated, solderable per MIL-STD-750,Method 2026
- Polarity : Indicated by cathode band
- Mounting Position : Any
- Weight : Approximated 0.07 gram

Package outline



Maximum ratings (AT $T_A=25^{\circ}\text{C}$ unless otherwise noted)

PARAMETER	SYMBOLS	FM201-AF	FM202-AF	FM203-AF	FM204-AF	FM205-AF	FM206-AF	FM207-AF	UNIT
Maximum repetitive peak reverse voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum average forward rectified current	I_o	2.0							A
Peak forward surge current 8.3ms single half sine-wave(JEDEC method)	I_{FSM}	50							A
Typical junction capacitance (Note 1)	C_J	30							pF
Operating junction temperature range	T_J	-55 to +150							$^{\circ}\text{C}$
Storage temperature range	T_{STG}	-55 to +150							$^{\circ}\text{C}$

Electrical characteristics (AT $T_A=25^{\circ}\text{C}$ unless otherwise noted)

PARAMETER	SYMBOLS	FM201-AF	FM202-AF	FM203-AF	FM204-AF	FM205-AF	FM206-AF	FM207-AF	UNIT
Maximum instantaneous forward voltage at $I_F=2.0\text{A}$	V_F	1.1							V
Maximum DC reverse current at rated DC blocking voltage	I_R	5.0 50.0							μA

Thermal characteristics

PARAMETER	SYMBOLS	FM201-AF	FM202-AF	FM203-AF	FM204-AF	FM205-AF	FM206-AF	FM207-AF	UNIT
Typical thermal resistance junction to ambient (Note 2)	$R_{\theta JA}$	50							$^{\circ}\text{C}/\text{W}$

Note1: Measured at 1MHz and applied reverse voltage of 4.0V D.C.

2: Thermal resistance from junction to ambient at 0.375" (9.5mm) lead length, P.C.B. mounted.

Rating and characteristic curves (FM201-AF THRU FM207-AF)

Fig.1 FORWARD CURRENT DERATING CURVE




Fig.2 TYPICAL FORWARD CHARACTERISTICS




Fig.3 MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT





Fig.4 TYPICAL REVERSE CHARACTERISTICS




FM201-AF THRU FM207-AF**Pinning information**

Pin	Simplified outline	Symbol
Pin1 cathode Pin2 anode		

Marking

Type number	Marking code
FM201-AF	GS2A,S2A
FM202-AF	GS2B,S2B
FM203-AF	GS2D,S2D
FM204-AF	GS2G,S2G
FM205-AF	GS2J,S2J
FM206-AF	GS2K,S2K
FM207-AF	GS2M,S2M


Suggested solder pad layout

Dimensions in inches and (millimeters)

PACKAGE	A	B	C
SMA-F	0.068 (1.70)	0.104 (2.60)	0.060(1.50)

FM201-AF THRU FM207-AF

Packing information



unit:mm


Item	Symbol	Tolerance	SMA-F
Carrier width	A	0.1	2.79
Carrier length	B	0.1	5.33
Carrier depth	C	0.1	2.36
Sprocket hole	d	0.1	1.50
13" Reel outside diameter	D	2.0	330.00
13" Reel inner diameter	D ₁	min	72.00
7" Reel outside diameter	D	2.0	178.00
7" Reel inner diameter	D ₁	min	62.00
Feed hole diameter	D ₂	0.5	13.00
Sprocket hole position	E	0.1	1.75
Punch hole position	F	0.1	5.50
Punch hole pitch	P	0.1	4.00
Sprocket hole pitch	P ₀	0.1	4.00
Embossment center	P ₁	0.1	2.00
Overall tape thickness	T	0.1	0.30
Tape width	W	0.3	12.00
Reel width	W ₁	1.0	18.00

Note: Devices are packed in accordance with EIA standard RS-481-A and specifications listed above.

Reel packing

PACKAGE	REEL SIZE	REEL (pcs)	COMPONENT SPACING (m/m)	BOX (pcs)	INNER BOX (m/m)	REEL DIA, (m/m)	CARTON SIZE (m/m)	CARTON (pcs)	APPROX. GROSS WEIGHT (kg)
SMA-F	13"	5,000	4.0	10,000	335*335*38	330	350*330*360	80,000	13.50

1.Storage environment: Temperature=5°C~40°C Humidity=55%±25%
2.Reflow soldering of surface-mount devices



Profile Feature	Soldering Condition
Average ramp-up rate(T_L to T_P)	$<3^{\circ}\text{C}/\text{sec}$
Preheat -Temperature Min(T_{min}) -Temperature Max(T_{max}) -Time(min to max)(t_s)	150°C 200°C $60\sim 120\text{sec}$
T_{max} to T_L -Ramp-upRate	$<3^{\circ}\text{C}/\text{sec}$
Time maintained above: -Temperature(T_L) -Time(t_L)	217°C $60\sim 260\text{sec}$
Peak Temperature(T_P)	$255^{\circ}\text{C}-0/+5^{\circ}\text{C}$
Time within 5°C of actual Peak Temperature(t_P)	$10\sim 30\text{sec}$
Ramp-down Rate	$<6^{\circ}\text{C}/\text{sec}$
Time 25°C to Peak Temperature	$<6\text{minutes}$

FM201-AF THRU FM207-AF

High reliability test capabilities

Item Test	Conditions	Reference
1. Solder Resistance	at $260 \pm 5^\circ\text{C}$ for $10 \pm 2\text{sec.}$ immerse body into solder $1/16" \pm 1/32"$	MIL-STD-750D METHOD-2031
2. Solderability	at $245 \pm 5^\circ\text{C}$ for 5 sec.	MIL-STD-202F METHOD-208
3. High Temperature Reverse Bias	$V_R = 80\%$ rate at $T_J = 150^\circ\text{C}$ for 168 hrs.	MIL-STD-750D METHOD-1038
4. Forward Operation Life	Rated average rectifier current at $T_A = 25^\circ\text{C}$ for 500hrs.	MIL-STD-750D METHOD-1027
5. Intermittent Operation Life	$T_A = 25^\circ\text{C}$, $I_F = I_O$ On state: power on for 5 min. off state: power off for 5 min. on and off for 500 cycles.	MIL-STD-750D METHOD-1036
6. Pressure Cooker	$15P_{SIG}$ at $T_A = 121^\circ\text{C}$ for 4 hrs.	JESD22-A102
7. Temperature Cycling	-55°C to $+125^\circ\text{C}$ dwelled for 30 min. and transferred for 5min. total 10 cycles.	MIL-STD-750D METHOD-1051
8. Forward Surge	8.3ms single half sine-wave , one surge.	MIL-STD-750D METHOD-4066-2
9. Humidity	at $T_A = 85^\circ\text{C}$, RH=85% for 1000hrs.	MIL-STD-750D METHOD-1021
10. High Temperature Storage Life	at 150°C for 1000 hrs.	MIL-STD-750D METHOD-1031