

FMOSAC83N10

List

List.....	1
Package outline.....	2
Features.....	2
Applications.....	2
Mechanical data.....	2
Maximum ratings	2
Electrical characteristics.....	3
Rating and characteristic curves.....	4~6
Pinning information.....	6
Marking.....	6
Packing information.....	7
Reel packing.....	8
Suggested thermal profiles for soldering processes.....	8

FMOSAC83N10

83A 100V N-Channel Enhancement Mode Power MOSFET

Features

- $V_{DS}=100V$, $I_D=83A$.
- $R_{DS(ON)} \leq 6.4m\Omega$, @ $V_{GS}=10V$, $I_D=20A$.
- $R_{DS(ON)} \leq 8.9m\Omega$, @ $V_{GS}=4.5V$, $I_D=15A$.
- Ultra-low on-resistance and low gate charge.
- 100% UIS and R_g tested.
- Lead-free parts meet RoHS requirements.
- Suffix "-H" indicates Halogen-free part, ex.FMOSAC83N10-H.


Applications

- Current switching in DC/DC & AC/DC (SR) sub systems.
- Motor driving in power tool, E-vehicle and robotics.
- Power management in Telecom., industrial automation and CE.

Mechanical data

- Epoxy:UL94-V0 rated flame retardant.
- Case : Molded plastic, T5060P8 (DFN5060-8).
- Mounting Position : Any.

Package outline



Maximum ratings (At $T_A=25^\circ C$ unless otherwise specified)

Parameter	Symbol	Ratings	Unit
Drain to source voltage	V_{DS}	100	V
Gate-source voltage	V_{GS}	± 20	V
Continuous drain Current (Note 1)	I_D	83	A
		52	
Pulsed drain current (Note 2)	I_{DM}	332	A
Single pulse avalanche energy (Note 3)	E_{AS}	216	mJ
Power dissipation (Note 4)	P_D	83	W
		33	
Thermal resistance-junction to ambient	$R_{\theta JA}$	50	$^\circ C/W$
Thermal resistance-junction to case	$R_{\theta JC}$	1.7	$^\circ C/W$
Junction temperature	T_J	+150	$^\circ C$
Storage temperature range	T_{STG}	-55 to +150	$^\circ C$

FMOSAC83N10

Electrical characteristics (At $T_J=25^\circ\text{C}$ unless otherwise noted)







Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Off characteristics						
Drain-source breakdown voltage	BV _{DSS}	I _D =250μA, V _{GS} =0V	100			V
Drain-source leakage current	I _{DSS}	V _{DS} =80V, V _{GS} =0V			1	μA
		V _{DS} =80V, V _{GS} =0V, T _J =55°C			5	
Gate-source leakage current	I _{GSS}	V _{DS} =0V, V _{GS} =±20V			±100	nA
On characteristics						
Gate threshold voltage	V _{GS(TH)}	V _{GS} =V _{DS} , I _D =250μA	1.2	2	2.5	V
Static drain-source on-resistance	R _{DS(ON)}	V _{GS} =10V, I _D =20A		5.3	6.4	mΩ
		V _{GS} =4.5V, I _D =15A		7.4	8.9	mΩ
Forward transconductance	g _{FS}	V _{DS} =5V, I _D =20A		33		S
Dynamic parameters (Note5)						
Input capacitance	C _{iss}	V _{GS} =0V, V _{DS} =50V, f=1.0MHz		2420		pF
Out capacitance	C _{oss}			900		
Reverse transfer capacitance	C _{rss}			35		
Gate resistance	R _G	V _{GS} =0V, V _{DS} =0V, f=1.0MHz		2.2		Ω
Switching parameters (Note5)						
Total gate charge	Q _g	V _{GS} =10V, V _{DS} =50V, I _D =20A		43		nC
		V _{GS} =4.5V, V _{DS} =50V, I _D =20A		22		
Gate to source charge	Q _{gs}	V _{GS} =0 to 10V, V _{DS} =50V, I _D =20A		9.4		
Gate to drain charge	Q _{gd}			10.3		
Turn-on delay time	t _{d(on)}	V _{GS} =10V, V _{DS} =50V, R _G =3Ω, R _L =2.5Ω		11.2		ns
Rise time	t _r			23		
Turn-off delay time	t _{d(off)}			38		
Fall time	t _f			15.3		
Source-drain diode ratings and characteristics						
Drain-source diode forward voltage	V _{SD}	I _S =1A, V _{GS} =0V		0.7	1	V
Diode Continuous Current	I _S	T _C =25°C			83	A
Body diode reverse recovery time	t _{rr}	I _F =20A, dI _F /dt =100A/μs		42		ns
Body diode reverse recovery charge	Q _{rr}			46		nC

Note :

1. Computed continuous current assumes the condition of T_{J_Max} while the actual continuous current depends on the thermal & electro-mechanical application board design.
2. This single-pulse measurement was taken under $T_{J_Max} = 150^\circ\text{C}$.
3. E_{AS} of 216 mJ is based on starting $T_J=25^\circ\text{C}$, $L=3\text{mH}$, $I_{AS}=12\text{A}$, $V_{GS}=10\text{V}$, $V_{DD}=50\text{V}$; 100% test at $L=0.1\text{mH}$, $I_{AS}=43\text{A}$.
4. The power dissipation P_D is based on $T_{J_Max} = 150^\circ\text{C}$.
5. This value is guaranteed by design hence it is not included in the production test.








FMOSAC83N10

Rating and characteristic curves





FMOSAC83N10

Rating and characteristic curves



FMOSAC83N10

Rating and characteristic curves




Pinning information

Pin	Simplified outline	Symbol
Pin 1, 2, 3 Source	Top view Bottom view	
Pin 4 Gate		
Pin 5, 6, 7, 8 Drain		

Marking


Type numbe	Marking code
FMOSAC83N10	SL1009P

Suggested solder pad layout



FMOSAC83N10

Packing information



unit:mm

Item	Symbol	Tolerance	T5060P8
Carrier width	A	0.1	6.40
Carrier length	B	0.1	5.40
Carrier depth	C	0.1	1.25
Sprocket hole	d	0.1	1.55
13" Reel outside diameter	D	2.0	330.00
13" Reel inner diameter	D1	2.0	100.00
7" Reel outside diameter	D	2.0	-
7" Reel inner diameter	D1	min	-
Feed hole diameter	D2	0.5	13.00
Sprocket hole position	E	0.1	1.75
Punch hole position	F	0.1	5.50
Punch hole pitch	P	0.1	8.00
Sprocket hole pitch	P0	0.1	4.00
Embossment center	P1	0.1	2.00
Overall tape thickness	T	0.1	0.30
Tape width	W	0.3	12.00

Note: Devices are packed in accordance with EIA standard RS-481-A and specifications listed above.


FMOSAC83N10

Reel packing

Device	Outline	Package	Reel Size	Reel (PCS)
FMOSAC83N10	TAPING	T5060P8	13inch	5,000

Suggested thermal profiles for soldering processes

- 1.Storage environment : Temperature=5°C~40°C Humidity=55%±25%
- 2.Reflow soldering of surface-mount devices



3.Reflow soldering

Profile feature	Soldering Condition
Average ramp-up rate (T_L to T_P)	< 3°C/sec
Prehaeat -Temperature Min (T_{smin}) -Temperature Max (T_{smax}) -Time (min to max) (t_s)	150°C 200°C 60 ~ 120sec
T_{smax} to T_L -Ramp-up rate	< 3°C/sec
Time maintained above: -Temperature (T_L) -Time(T_L)	217°C 60 ~ 260 sec
Peak Temperature(T_P)	255°C -0/+5°C
Time within 5°C of actual peak Temperature(T_P)	10 ~ 30sec
Ramp-down rate	< 6°C/sec
Time 25°C to peak temperature	< 6 minutes