

FMOSBSS8402DW

List

List.....	1
Package outline.....	2
Features.....	2
Applications.....	2
Mechanical data.....	2
Maximum ratings	2
Electrical characteristics.....	3~4
Rating and characteristic curves (N-Channel).....	5
Rating and characteristic curves (P-Channel).....	6
Pinning information.....	7
Marking.....	7
Packing information.....	8
Reel packing.....	9
Suggested thermal profiles for soldering processes.....	9

FMOSBSS8402DW

N-Channel And P-Channel Enhancement Mode MOSFET


Features

- N-Channel : 60V / 115mA.
 $R_{DS(ON)} \leq 3.0\Omega$, @ $V_{GS}=10V$, $I_D=0.13A$
 $R_{DS(ON)} \leq 3.5\Omega$, @ $V_{GS}=4.5V$, $I_D=0.1A$
- P-Channel : -50V/-130mA.
 $R_{DS(ON)} \leq 10\Omega$, @ $-V_{GS}=5V$, $-I_D=0.1A$.
- Low on-resistance.
- Low gate threshold voltage.
- Fast switching.
- Lead-free parts meet RoHS requirements.
- Suffix "-H" indicates Halogen-free part, ex.FMOSBSS8402DW-H.

Mechanical data

- Epoxy:UL94-V0 rated flame retardant.
- Case : Molded plastic, SOT-363.
- Terminals : Solder plated, solder able per MIL-STD-750, Method 2026.
- Mounting Position : Any.

Package outline



Maximum ratings (At $T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Ratings		Unit
		N-Channel	P-Channel	
Drain to source voltage	V_{DS}	60	-50	V
Gate-source voltage	V_{GS}	± 20	± 20	V
		± 40	-	
Drain to Gate voltage, ($R_{GS} \leq 1m\Omega$ for N-Ch) ; ($R_{GS} \leq 20K\Omega$ for P-Ch)	V_{DGR}	60	-50	V
Continuous drain current (Note1)	I_D	115	-130	mA
		73	—	
		800	—	
Power dissipation (Note1)	P_D	200		mW
Thermal resistance, junction to ambient	$R_{\theta JA}$	625		$^\circ\text{C/W}$
Junction temperature	T_J	+150		$^\circ\text{C}$
Storage temperature range	T_{STG}	-55 to +150		$^\circ\text{C}$

Note: 1. FR-5 board 1.0x0.75x0.062 inch with minimum recommended pad layout.

FMOSBSS8402DW

Electrical characteristics (At $T_A=25^{\circ}\text{C}$ unless otherwise specified)

N-Channel

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Static parameters (Note2)						
Drain-source breakdown voltage	BV _{DSS}	I _D =10μA, V _{GS} =0V	60	70		V
Drain-source leakage current	I _{DSS}	V _{DS} =60V, V _{GS} =0V, T _C =+25°C			1	μA
		V _{DS} =60V, V _{GS} =0V, T _C =+125°C			500	
Gate-source leakage current	I _{GSS}	V _{GS} =±20V, V _{DS} =0V			±100	nA
On characteristics (Note2)						
Gate threshold voltage	V _{GS(TH)}	V _{DS} =V _{GS} , I _D =250μA	1.0		2.5	V
Static drain-source on-state resistance	R _{DS(ON)}	V _{GS} =10V, I _D =0.13A		1.5	3	Ω
		V _{GS} =4.5V, I _D =0.1A		1.8	3.5	
Forward tranconductance	g _{FS}	V _{DS} =10V, I _D =0.2A	80			mS
Dynamic parameters						
Input capacitance	C _{iss}	V _{GS} =0V, V _{DS} =25V, f=1.0MHz		22	50	pF
Out capacitance	C _{oss}			11	25	
Reverse transfer capacitance	C _{rss}			2	5	
Switching parameters						
Turn-on delay time	t _{d(on)}	V _{DS} =30V, I _D =0.2A, R _G =25Ω, R _L =150Ω, V _G =10V		7	20	ns
Turn-off delay time	t _{d(off)}			11	20	ns

Note: 2. Short duration test pulse used to minimize self-heating.

FMOSBSS8402DW

Electrical characteristics (At $T_c=25^\circ\text{C}$ unless otherwise specified)









P-Channel

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Static parameters (Note2)						
Drain-source breakdown voltage	$-BV_{DSS}$	$-I_D=250\mu A, V_{GS}=0V$	50			V
Drain-source leakage current	$-I_{DSS}$	$-V_{DS}=50V, V_{GS}=0V, T_J=+25^{\circ}C$			1	μA
		$-V_{DS}=50V, V_{GS}=0V, T_J=+125^{\circ}C$			2	
		$-V_{DS}=25V, V_{GS}=0V, T_J=+25^{\circ}C$			100	nA
Gate-source leakage current	I_{GSS}	$V_{GS}=\pm 20V, V_{DS}=0V$			± 100	nA
On characteristics (Note2)						
Gate threshold voltage	$-V_{GS(TH)}$	$V_{DS}=V_{GS}, -I_D=1mA$	0.8		2	V
Static drain-source on-state resistance	$R_{DS(ON)}$	$-V_{GS}=5V, -I_D=0.1A$			10	Ω
Forward tranconductance	g_{FS}	$-V_{DS}=25V, -I_D=0.1A$	0.05			S
Dynamic parameters						
Input capacitance	C_{iss}	$V_{GS}=0V, -V_{DS}=25V, f=1.0MHz$			45	pF
Out capacitance	C_{oss}				25	
Reverse transfer capacitance	C_{rss}				12	
Switching parameters						
Turn-on delay time	$t_{d(on)}$	$-V_{DS}=30V, -I_D=0.27A, R_G=50\Omega, V_G=-10V$		10		ns
Turn-off delay time	$t_{d(off)}$			18		ns

Note: 2. Short duration test pulse used to minimize self-heating.


FMOSBSS8402DW

Rating and characteristic curves (N-Channel)





FMOSBSS8402DW

Rating and characteristic curves (P-Channel)



FMOSBSS8402DW


Pinning information

Pin	Simplified outline	Symbol
Pin1 Source1 Pin2 Gate1 Pin3 Drain2 Pin4 Source2 Pin5 Gate2 Pin6 Drain1		

Marking


Type number	Marking code
FMOSBSS8402DW	S82

Suggested solder pad layout



FMOSBSS8402DW

Packing information



unit:mm

Item	Symbol	Tolerance	SOT-363
Carrier width	A	0.2	2.25
Carrier length	B	0.2	2.55
Carrier depth	C	0.1	1.20
Sprocket hole	d	0.1	1.50
13" Reel outside diameter	D	2.0	-
13" Reel inner diameter	D1	min	-
7" Reel outside diameter	D	2.0	178.00
7" Reel inner diameter	D1	min	62.00
Feed hole diameter	D2	0.5	13.00
Sprocket hole position	E	0.1	1.75
Punch hole position	F	0.1	3.50
Punch hole pitch	P	0.1	4.00
Sprocket hole pitch	P0	0.1	4.00
Embossment center	P1	0.1	2.00
Overall tape thickness	T	0.1	0.23
Tape width	W	0.3	8.00
Reel width	W1	1.0	11.40

Note: Devices are packed in accordance with EIA standard RS-481-A and specifications listed above.


FMOSBSS8402DW

Reel packing

PACKAGE	REEL SIZE	REEL (pcs)	COMPONENT SPACING (m/m)	BOX (pcs)	INNER BOX (m/m)	REEL DIA, (m/m)	CARTON SIZE (m/m)	CARTON (pcs)
SOT-363	7"	3,000	4.0	30,000	183*123*183	178	382*257*387	240,000

Suggested thermal profiles for soldering processes

- 1.Storage environment : Temperature=5°C~40°C Humidity=55%±25%
- 2.Reflow soldering of surface-mount devices



3.Reflow soldering

Profile feature	Soldering Condition
Average ramp-up rate (T_L to T_p)	< 3°C/sec
Preheat -Temperature Min (T_{smin}) -Temperature Max (T_{smax}) -Time (min to max) (t_s)	150°C 200°C 60 ~ 120sec
T_{smax} to T_L -Ramp-up rate	< 3°C/sec
Time maintained above: -Temperature (T_L) -Time(T_L)	217°C 60 ~ 260 sec
Peak Temperature(T_p)	255°C -0/+5°C
Time within 5°C of actual peak Temperature(T_p)	10 ~ 30sec
Ramp-down rate	< 6°C/sec
Time 25°C to peak temperature	< 6 minutes