

FM120-BF THRU FM1200-BF**List**

List.....	1
Package outline.....	2
Features.....	2
Mechanical data.....	2
Maximum ratings	2
Electrical characteristics.....	2
Rating and characteristic curves.....	3
Pinning information.....	4
Marking.....	4
Suggested solder pad layout.....	4
Packing information.....	5
Reel packing.....	6
Suggested thermal profiles for soldering processes.....	6
High reliability test capabilities.....	7

FM120-BF THRU FM1200-BF

1.0A Surface Mount Schottky Barrier Rectifiers 20-200V


Features

- Low power loss, high efficiency
- High current capability, low forward voltage drop
- Ultra high-speed switching
- Silicon epitaxial planar chip, metal silicon junction
- Lead-free parts meet RoHS requirements
- Suffix "-H" indicates Halogen free parts, ex. FM120-BF-H

Mechanical data

- Epoxy: UL94-V0 rated flame retardant
- Case : Molded plastic, DO-214AA / SMB-F
- Terminals : Solder plated, solderable per MIL-STD-750, Method 2026
- Polarity : Indicated by cathode band
- Mounting Position : Any
- Weight : Approximated 0.098 gram

Package outline



Maximum ratings (AT $T_A=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbols	FM120-BF	FM140-BF	FM160-BF	FM1100-BF	FM1150-BF	FM1200-BF	Units
Maximum repetitive peak reverse voltage	VRRM	20	40	60	100	150	200	V
Maximum RMS voltage	VRMS	14	28	42	70	105	140	V
Maximum DC blocking voltage	VDC	20	40	60	100	150	200	V
Maximum average forward rectified current at T _L (see fig. 1)	I _o	1.0						A
Peak forward surge current, 8.3ms single half-sine-wave (JEDEC method)	I _{FSM}	30						A
Operating junction temperature range	T _J	-55 to +125		-55 to +150				°C
Storage temperature range	T _{STG}	-55 to +150						°C

Electrical characteristics (AT $T_A=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbols	FM120-BF	FM140-BF	FM160-BF	FM1100-BF	FM1150-BF	FM1200-BF	Units
Maximum forward voltage at IF=1.0A	VF	0.55		0.70	0.85	0.95		V
Maximum reverse current at TA = 25°C at rated DC blocking voltage TA=125°C	IR	0.5 50			0.05 10			mA

Thermal characteristics

Parameter	Symbols	FM120-BF	FM140-BF	FM160-BF	FM1100-BF	FM1150-BF	FM1200-BF	Units
Typical thermal resistance junction to ambient	$R_{\theta JA}$	88						$^{\circ}\text{C/W}$

Rating and characteristic curves (FM120-BF THRU FM1200-BF)

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-TYPICAL FORWARD CHARACTERISTICS




FIG.3-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.4-TYPICAL JUNCTION CAPACITANCE





FIG.5 - TYPICAL REVERSE CHARACTERISTICS



FM120-BF THRU FM1200-BF


Pinning information

Pin	Simplified outline	Symbol
Pin1 cathode Pin2 anode		

Marking

Type number	Marking code
FM120-BF	SS12
FM140-BF	SS14
FM160-BF	SS16
FM1100-BF	SS110
FM1150-BF	SS115,SS1150
FM1200-BF	SS120,SS1200

Suggested solder pad layout




Dimensions in inches and (millimeters)

PACKAGE	A	B	C
SMB-F	0.091 (2.30)	0.098 (2.50)	0.071 (1.80)

FM120-BF THRU FM1200-BF

Packing information



unit:mm

Item	Symbol	Tolerance	SMB-F
Carrier width	A	0.1	3.80
Carrier length	B	0.1	5.40
Carrier depth	C	0.1	2.45
Sprocket hole	d	0.1	1.55
13" Reel outside diameter	D	2.0	330.00
13" Reel inner diameter	D1	min	50.00
7" Reel outside diameter	D	2.0	178.00
7" Reel inner diameter	D1	min	62.00
Feed hole diameter	D2	0.5	13.00
Sprocket hole position	E	0.1	1.75
Punch hole position	F	0.1	5.50
Punch hole pitch	P	0.1	8.00
Sprocket hole pitch	P0	0.1	4.00
Embossment center	P1	0.1	2.00
Overall tape thickness	T	0.015	0.40
Tape width	W	0.3	12.00
Reel width	W1	1.0	18.00

Note: Devices are packed in accordance with EIA standard RS-481-A and specifications listed above.


FM120-BF THRU FM1200-BF

Reel packing

PACKAGE	REEL SIZE	REEL (pcs)	COMPONENT SPACING (m/m)	BOX (pcs)	INNER BOX (m/m)	REEL DIA, (m/m)	CARTON SIZE (m/m)	CARTON (pcs)	APPROX. GROSS WEIGHT (kg)
SMB-F	13"	3,000	8.0	6,000	335*335*38	330	350*330*360	48,000	12.40

Suggested thermal profiles for soldering processes

- 1.Storage environment: Temperature=5°C~40°C Humidity=55%±25%
- 2.Reflow soldering of surface-mount devices



3.Reflow soldering

Profile Feature	Soldering Condition
Average ramp-up rate(T _L to T _P)	<3°C/sec
Preheat -Temperature Min(T _{smmin}) -Temperature Max(T _{smmax}) -Time(min to max)(t _s)	150°C 200°C 60~120sec
T _{smmax} to T _L -Ramp-upRate	<3°C/sec
Time maintained above: -Temperature(T _L) -Time(t _L)	217°C 60~260sec
Peak Temperature(T _P)	255°C-0/+5°C
Time within 5°C of actual Peak Temperature(t _p)	10~30sec
Ramp-down Rate	<6°C/sec
Time 25°C to Peak Temperature	<6minutes

FM120-BF THRU FM1200-BF**High reliability test capabilities**

Item Test	Conditions	Reference
1. Solder Resistance	at $260 \pm 5^\circ\text{C}$ for $10 \pm 2\text{sec}$.	MIL-STD-750D METHOD-2031
2. Solderability	at $245 \pm 5^\circ\text{C}$ for 5 sec.	MIL-STD-202F METHOD-208
3. High Temperature Reverse Bias	$V_R = 80\%$ rate at $T_J = 125^\circ\text{C}$ for 168 hrs.	MIL-STD-750D METHOD-1038
4. Forward Operation Life	Rated average rectifier current at $T_A = 25^\circ\text{C}$ for 500hrs.	MIL-STD-750D METHOD-1027
5. Intermittent Operation Life	$T_A = 25^\circ\text{C}$, $I_F = I_O$ On state: power on for 5 min. off state: power off for 5 min. on and off for 500 cycles.	MIL-STD-750D METHOD-1036
6. Pressure Cooker	$15P_{SIG}$ at $T_A = 121^\circ\text{C}$ for 4 hrs.	JESD22-A102
7. Temperature Cycling	-55°C to $+125^\circ\text{C}$ dwelled for 30 min. and transferred for 5min. total 10 cycles.	MIL-STD-750D METHOD-1051
8. Forward Surge	8.3ms single half sine-wave , one surge.	MIL-STD-750D METHOD-4066-2
9. Humidity	at $T_A = 85^\circ\text{C}$, RH=85% for 1000hrs.	MIL-STD-750D METHOD-1021
10. High Temperature Storage Life	at 150°C for 1000 hrs.	MIL-STD-750D METHOD-1031