

# FM1220-T7B THRU FM12200-T7B

## List

|                                                         |   |
|---------------------------------------------------------|---|
| List.....                                               | 1 |
| Package outline.....                                    | 2 |
| Features.....                                           | 2 |
| Mechanical data.....                                    | 2 |
| Maximum ratings and Electrical characteristics.....     | 2 |
| Rating and characteristic curves.....                   | 3 |
| Pinning information.....                                | 4 |
| Marking.....                                            | 4 |
| Suggested solder pad layout.....                        | 4 |
| Packing information.....                                | 5 |
| Reel packing.....                                       | 6 |
| Suggested thermal profiles for soldering processes..... | 6 |
| High reliability test capabilities.....                 | 7 |

# FM1220-T7B THRU FM12200-T7B

## 12.0A Surface Mounted Schottky Barrier Rectifiers 20V-200V


### Features

- For surface mounted applications
- Built-in strain relief, ideal for automated placement.
- Low reverse leakage
- High forward surge current capability
- Lead free finish, RoHS compliant
- Suffix "-H" indicates Halogen free parts, ex. FM1220-T7B-H

### Mechanical data

- Epoxy:UL94-V0 rated flame retardant
- Case : Molded plastic, TO-277B
- Terminals : Solder plated, solderable per MIL-STD-750, Method 2026
- Polarity : Polarity symbol marking on body
- Mounting Position : Any
- Weight : Approximated 0.092gram

### Package outline



### Maximum ratings (AT $T_A=25^{\circ}\text{C}$ unless otherwise noted)

| Parameter                                                                | Symbols   | FM1220-T7B  | FM1240-T7B | FM1260-T7B | FM1280-T7B | FM12100-T7B | FM12150-T7B | FM12200-T7B | Unit               |
|--------------------------------------------------------------------------|-----------|-------------|------------|------------|------------|-------------|-------------|-------------|--------------------|
| Repetitive peak reverse voltage                                          | $V_{RRM}$ | 20          | 40         | 60         | 80         | 100         | 150         | 200         | V                  |
| RMS voltage                                                              | $V_{RMS}$ | 14          | 28         | 42         | 56         | 70          | 105         | 140         | V                  |
| Continuous reverse voltage                                               | $V_R$     | 20          | 40         | 60         | 80         | 100         | 150         | 200         | V                  |
| Average forward rectified current                                        | $I_o$     | 12.0        |            |            |            |             |             |             | A                  |
| Non-repetitive peak forward surge current<br>8.3ms single half sine-wave | $I_{FSM}$ | 200         |            |            |            |             |             |             | A                  |
| Operating junction temperature range                                     | $T_J$     | -55 to +150 |            |            |            |             |             |             | $^{\circ}\text{C}$ |
| Storage temperature range                                                | $T_{STG}$ | -55 to +150 |            |            |            |             |             |             | $^{\circ}\text{C}$ |





### Maximum electrical characteristics (AT $T_A=25^{\circ}\text{C}$ unless otherwise noted)

| Parameter                                                                 | Symbols | FM1220-T7B | FM1240-T7B | FM1260-T7B | FM1280-T7B | FM12100-T7B | FM12150-T7B | FM12200-T7B | Unit |
|---------------------------------------------------------------------------|---------|------------|------------|------------|------------|-------------|-------------|-------------|------|
| Forward voltage at $I_F=12.0A$                                            | $V_F$   | 0.55       |            | 0.70       | 0.85       |             | 0.95        |             | V    |
| Reverse current at rated $V_R$<br>$T_J=25^{\circ}C$<br>$T_J=125^{\circ}C$ | $I_R$   | 0.5<br>50  |            |            | 0.05<br>10 |             |             |             | mA   |


### Thermal characteristics

| Parameter                                         | Symbols         | FM1220-T7B | FM1240-T7B | FM1260-T7B | FM1280-T7B | FM12100-T7B | FM12150-T7B | FM12200-T7B | Unit                        |
|---------------------------------------------------|-----------------|------------|------------|------------|------------|-------------|-------------|-------------|-----------------------------|
| Typical thermal resistance<br>junction to ambient | $R_{\theta JA}$ | 60.0       |            |            |            |             |             |             | $^{\circ}\text{C}/\text{W}$ |

## Rating and characteristic curves (FM1220-T7B THRU FM12200-T7B)




**FM1220-T7B THRU FM12200-T7B****Pinning information**

| Pin                                         | Simplified outline                                                                | Symbol                                                                              |
|---------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| PIN 1 anode<br>PIN 3 anode<br>PIN 2 cathode |  |  |

**Marking**


| Type Number | Marking Code |
|-------------|--------------|
| FM1220-T7B  | SS1220       |
| FM1240-T7B  | SS1240       |
| FM1260-T7B  | SS1260       |
| FM1280-T7B  | SS1280       |
| FM12100-T7B | SS12100      |
| FM12150-T7B | SS12150      |
| FM12200-T7B | SS12200      |

**Suggested solder pad layout****TO-277B**

Dimensions in inches and (millimeters)

## FM1220-T7B THRU FM12200-T7B

## Packing information



unit:mm

| Item                      | Symbol | Tolerance | TO-277B |
|---------------------------|--------|-----------|---------|
| Carrier width             | A      | 0.1       | 4.40    |
| Carrier length            | B      | 0.1       | 6.90    |
| Carrier depth             | C      | 0.1       | 1.30    |
| Sprocket hole             | d      | 0.1       | 1.55    |
| 13" Reel outside diameter | D      | 2.0       | 330.00  |
| 13" Reel inner diameter   | D1     | min       | 50.00   |
| 7" Reel outside diameter  | D      | 2.0       | 178.00  |
| 7" Reel inner diameter    | D1     | min       | 62.00   |
| Feed hole diameter        | D2     | 0.5       | 13.00   |
| Sprocket hole position    | E      | 0.1       | 1.75    |
| Punch hole position       | F      | 0.1       | 7.50    |
| Punch hole pitch          | P      | 0.1       | 8.00    |
| Sprocket hole pitch       | P0     | 0.1       | 4.00    |
| Embossment center         | P1     | 0.1       | 2.00    |
| Overall tape thickness    | T      | 0.1       | 0.25    |
| Tape width                | W      | 0.3       | 12.00   |
| Reel width                | W1     | 1.0       | 14.00   |

Note: Devices are packed in accordance with EIA standard RS-481-A and specifications listed above.


## FM1220-T7B THRU FM12200-T7B

## Reel packing

| PACKAGE | REEL SIZE | REEL (pcs) | COMPONENT SPACING (m/m) | BOX (pcs) | INNER BOX (m/m) | REEL DIA, (m/m) | CARTON SIZE (m/m) | CARTON (pcs) | APPROX. GROSS WEIGHT (kg) |
|---------|-----------|------------|-------------------------|-----------|-----------------|-----------------|-------------------|--------------|---------------------------|
| TO-277B | 13"       | 5,000      | 8.0                     | 10,000    | 335*335*38      | 330             | 350*330*360       | 80,000       | 18.0                      |

## Suggested thermal profiles for soldering processes

- 1.Storage environment: Temperature=5°C~40°C Humidity=55%±25%
- 2.Reflow soldering of surface-mount devices



## 3.Reflow soldering

| Profile Feature                                                                                                               | Soldering Condition         |
|-------------------------------------------------------------------------------------------------------------------------------|-----------------------------|
| Average ramp-up rate(T <sub>L</sub> to T <sub>P</sub> )                                                                       | <3°C/sec                    |
| Preheat<br>-Temperature Min(T <sub>smin</sub> )<br>-Temperature Max(T <sub>smax</sub> )<br>-Time(min to max)(t <sub>s</sub> ) | 150°C<br>200°C<br>60~120sec |
| T <sub>smax</sub> to T <sub>L</sub><br>-Ramp-upRate                                                                           | <3°C/sec                    |
| Time maintained above:<br>-Temperature(T <sub>L</sub> )<br>-Time(t <sub>L</sub> )                                             | 217°C<br>60~260sec          |
| Peak Temperature(T <sub>P</sub> )                                                                                             | 255°C-0/+5°C                |
| Time within 5°C of actual Peak Temperature(t <sub>P</sub> )                                                                   | 10~30sec                    |
| Ramp-down Rate                                                                                                                | <3°C/sec                    |
| Time 25°C to Peak Temperature                                                                                                 | <6minutes                   |

**FM1220-T7B THRU FM12200-T7B****High reliability test capabilities**

| Item Test                         | Conditions                                                                                                                               | Reference                     |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|
| 1. Solder Resistance              | at $260 \pm 5^\circ\text{C}$ for $10 \pm 2\text{sec.}$                                                                                   | MIL-STD-750D<br>METHOD-2031   |
| 2. Solderability                  | at $245 \pm 5^\circ\text{C}$ for 5 sec.                                                                                                  | MIL-STD-202F<br>METHOD-208    |
| 3. High Temperature Reverse Bias  | $V_R = 80\%$ rate at $T_J = 150^\circ\text{C}$ for 168 hrs.                                                                              | MIL-STD-750D<br>METHOD-1038   |
| 4. Forward Operation Life         | Rated average rectifier current at $T_A = 25^\circ\text{C}$ for 500hrs.                                                                  | MIL-STD-750D<br>METHOD-1027   |
| 5. Intermittent Operation Life    | $T_A = 25^\circ\text{C}$ , $I_F = I_O$<br>On state: power on for 5 min.<br>off state: power off for 5 min.<br>on and off for 500 cycles. | MIL-STD-750D<br>METHOD-1036   |
| 6. Pressure Cooker                | $15P_{SIG}$ at $T_A = 121^\circ\text{C}$ for 4 hrs.                                                                                      | JESD22-A102                   |
| 7. Temperature Cycling            | $-55^\circ\text{C}$ to $+125^\circ\text{C}$ dwelled for 30 min.<br>and transferred for 5min. total 10 cycles.                            | MIL-STD-750D<br>METHOD-1051   |
| 8. Forward Surge                  | 8.3ms single half sine-wave , one surge.                                                                                                 | MIL-STD-750D<br>METHOD-4066-2 |
| 9. Humidity                       | at $T_A = 85^\circ\text{C}$ , RH=85% for 1000hrs.                                                                                        | MIL-STD-750D<br>METHOD-1021   |
| 10. High Temperature Storage Life | at $175^\circ\text{C}$ for 1000 hrs.                                                                                                     | MIL-STD-750D<br>METHOD-1031   |