

MBR1040CTW THRU MBR10200CTW

List

List..... 1

Package outline..... 2

Features..... 2

Mechanical data..... 2

Maximum ratings2

Rating and characteristic curves..... 3

Pinning information.....4

Marking..... 4

Tube packing.....4

Suggested thermal profiles for soldering processes..... 5

High reliability test capabilities.....6

MBR1040CTW THRU MBR10200CTW

10A High Barrier Power Schottky
Rectifiers : 40V-200V


Features

- 150°C operating junction temperature.
- Low power loss, high efficiency.
- High current capability
- High surge capability.
- Guardring for overvoltage protection.
- Low stored charge majority carrier conduction
- Silicon epitaxial planar chip, metal silicon junction.
- Lead-free parts meet environmental standards of MIL-STD-19500 /228
- Suffix "-H" indicates Halogen-free parts, ex. MBR1040CTW-H.

Mechanical data

- Epoxy : UL94-V0 rated flame retardant
- Case : JEDEC TO-220AB molded plastic body over passivated chip
- Lead : Axial leads, solderable per MIL-STD-202, Method 208 guaranteed
- Polarity: As marked
- Mounting Position : Any
- Weight : TO-220AB Approximated 1.85gram

Package outline



Maximum Ratings (AT $T_A=25^{\circ}\text{C}$ unless otherwise noted)

PARAMETER	SYMBOLS	MBR 1040CTW	MBR 1045CTW	MBR 1060CTW	MBR 10100CTW	MBR 10150CTW	MBR 10200CTW	UNIT
Repetitive peak reverse voltage	VRRM	40	45	60	100	150	200	V
RMS voltage	VRMS	28	31.5	42	70	105	140	V
DC blocking voltage	VDC	40	45	60	100	150	200	V
Average forward rectified current per device per diode	Io	10 5						A
Peak forward surge current 8.3ms single half sine-wave(JEDEC method)	IFSM	125						A
Operating junction temperature range	TJ	-55 to +150				-55 to +175		°C
Storage temperature range	TSTG	-55 to +175						°C

Maximum Electrical Characteristics (AT $T_A=25^{\circ}\text{C}$ unless otherwise noted)

PARAMETER	SYMBOLS	MBR 1040CTW	MBR 1045CTW	MBR 1060CTW	MBR 10100CTW	MBR 10150CTW	MBR 10200CTW	UNIT
Forward voltage per leg at If=5A	V _F	0.65		0.75	0.85	0.95		V
DC reverse current at T _J =25°C at rated DC blocking voltage at T _J =125°C	I _R	0.10 12			0.01 6			mA

Thermal Characteristics

PARAMETER	SYMBOLS	MBR 1040CTW	MBR 1045CTW	MBR 1060CTW	MBR 10100CTW	MBR 10150CTW	MBR 10200CTW	UNIT
Typical thermal resistance junction to case per leg	$R_{\theta JC}$	2.0						$^{\circ}\text{C/W}$

Rating and characteristic curves (MBR1040CTW THRU MBR10200CTW)

FIG.1-DERATING CURVE OUTPUT RECTIFIED CURRENT




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL REVERSE LEAKAGE CHARACTERISTICS







FIG.4-TYPICAL FORWARD VOLTAGE CHARACTERISTICS



MBR1040CTW THRU MBR10200CTW**Pinning information**


Pin	Simplified outline	Symbol
Pin1 anode Pin2 cathode Pin3 anode		

Marking

Type number	Marking code
MBR1040CTW	MBR1040CTW
MBR1045CTW	MBR1045CTW
MBR1060CTW	MBR1060CTW
MBR10100CTW	MBR10100CTW
MBR10150CTW	MBR10150CTW
MBR10200CTW	MBR10200CTW

Tube packing

PACKAGE	TUBE (pcs)	TUBE SIZE (m/m)	BOX (pcs)	INNER BOX (m/m)	CARTON SIZE (m/m)	CARTON (pcs)	APPROX. GROSS WEIGHT (kg)
TO-220AB	50	525*31.9*6.4	1000	545*150*45	575*245*170	5,000	15.0

MBR1040CTW THRU MBR10200CTW**Suggested thermal profiles for soldering processes****1. Lead free temperature profile wave-soldering**

MBR1040CTW THRU MBR10200CTW**High reliability test capabilities**

Item Test	Conditions	Reference
1. Solder Resistance	at $260\pm5^{\circ}\text{C}$ for $10\pm2\text{sec.}$ immerse body into solder $1/16''\pm1/32''$	MIL-STD-750D METHOD-2031
2. Solderability	at $245\pm5^{\circ}\text{C}$ for 5 sec.	MIL-STD-202F METHOD-208
3. High Temperature Reverse Bias	$V_R=80\%$ rate at $T_J=150^{\circ}\text{C}$ for 168 hrs.	MIL-STD-750D METHOD-1038
4. Forward Operation Life	Rated average rectifier current at $T_A=25^{\circ}\text{C}$ for 500hrs.	MIL-STD-750D METHOD-1027
5. Intermittent Operation Life	$T_A = 25^{\circ}\text{C}$, $I_F = I_O$ On state: power on for 5 min. off state: power off for 5 min. on and off for 500 cycles.	MIL-STD-750D METHOD-1036
6. Pressure Cooker	$15P_{SIG}$ at $T_A=121^{\circ}\text{C}$ for 4 hrs.	JESD22-A102
7. Temperature Cycling	-55°C to $+125^{\circ}\text{C}$ dwelled for 30 min. and transferred for 5min. total 10 cycles.	MIL-STD-750D METHOD-1051
8. Forward Surge	8.3ms single half sine-wave , one surge.	MIL-STD-750D METHOD-4066-2
9. Humidity	at $T_A=85^{\circ}\text{C}$, RH=85% for 1000hrs.	MIL-STD-750D METHOD-1021
10. High Temperature Storage Life	at 175°C for 1000 hrs.	MIL-STD-750D METHOD-1031